

GH493 四层钢丝缠绕软管

符合或超过 SAE 100R12,
EN 856 Type R12, ISO 3862 Type R12,
EN 856 4SP performance (-8 thru -16)



高性能



GH493-6 9.5 mm (0.38 in) DN10 **Dura-Tuff** Exceeds SAE 100R12 / EN856 R12 MSHA IC-84/19 - ABS - DNV - USCG + **448 BAR (6500 PSI)** -40°C to +126°C -40°F to +260°F Half Bend 4S

结构: 合成橡胶内层，四层高强度钢丝缠绕增强层，蓝色 Dura-Tuff™ 高耐磨合成橡胶外层。

PART #	SIZE DIMENSIONS				PRESSURE				BEND		WEIGHT	
	Hose I.D.		Hose O.D. (nominal)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
GH493-6	9.5	0.38	20.2	0.80	448	6,500	1,792	26,000	62.5	2.46	0.71	0.48
GH493-8	12.7	0.50	23.6	0.93	415	6,000	1,660	24,000	90.0	3.54	0.87	0.59
GH493-10	15.9	0.62	27.4	1.08	415	6,000	1,660	24,000	100	3.94	1.00	0.68
GH493-12	19.0	0.75	30.7	1.21	380	5,500	1,520	22,000	120	4.72	1.34	0.90
GH493-16	25.4	1.00	37.9	1.49	350	5,100	1,400	20,400	150	5.91	1.78	1.20
GH493-20	31.8	1.25	46.6	1.84	310	4,500	1,240	18,000	210	8.27	2.41	1.62
GH493-24	38.1	1.50	53.9	2.12	275	4,000	1,100	16,000	250	9.84	3.00	2.01
GH493-32	50.8	2.00	66.8	2.63	275	4,000	1,100	16,000	320	12.60	4.37	2.94

工作温度范围: -40°C 到 +126°C (-40°F 到 +260°F)

匹配接头: 1A • 4S

应用:

石油基或水基液压油的液压系统，适用各种工业行业。如有其它特殊应用需求，请联系 Danfoss。

行业认证:

MSHA
ABS