

EC215 二层钢丝编织软管

符合 EN857 2SC



Winner by Danfoss **EC215-06** 9.5 MM (0.38 IN) DN10 | EN857 2SC • ISO 18752 | MSHA IC-84/41 • DNV • USCG | **345 BAR (5000 PSI)** | -40°C to +100°C / -40°F to +212°F | Half Bend | 1A • Z | 2R • 2PC

结构: 合成橡胶内层，二层钢丝编织增强层，黑色合成橡胶外层。

PART #	SIZE DIMENSIONS				PRESSURE				BEND		WEIGHT	
	Hose I.D.		Hose O.D. (nominal)		Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
EC215-04	6.4	0.25	14.2	0.56	400	5,800	1,600	23,200	50	1.97	0.28	0.19
EC215-05	7.9	0.31	16.0	0.63	350	5,100	1,400	20,400	55	2.17	0.33	0.22
EC215-06	9.5	0.37	18.3	0.72	330	4,800	1,320	19,200	65	2.56	0.41	0.28
EC215-08	12.7	0.50	21.5	0.85	275	4,000	1,100	16,000	90	3.54	0.57	0.38
EC215-10	15.9	0.63	24.7	0.97	250	3,650	1,000	14,600	100	3.94	0.68	0.46
EC215-12	19.0	0.75	28.6	1.13	215	3,125	860	12,500	120	4.72	0.81	0.54
EC215-16	25.4	1.00	36.6	1.44	165	2,400	660	9,600	160	6.30	1.17	0.79
EC215-20	31.8	1.25	45.1	1.78	125	1,800	500	7,200	250	9.84	1.56	1.05
EC215-24	38.1	1.50	52.3	2.06	100	1,450	400	5,800	300	11.81	1.81	1.22
EC215-32	50.8	2.00	64.2	2.53	90	1,300	360	5,200	400	15.75	2.36	1.59

工作温度范围: -40°C 到 +100°C (-40°F 到 +212°F)

匹配接头: 1A/Z 系列 | Winner 分体式接头 | 2R 系列可拆式接头

应用:

石油基或水基液压油的液压系统，适用各种工业行业。如有其它特殊应用需求，请联系 Danfoss。

行业认证:

MSHA
DNV
USCG